



Perfect for many current measurement situations

The new Fluke 374 clamp meters offer improved performance perfect for many current measurement situations. With true-rms ac voltage and current measurements, the Fluke 374 can read up to 600 V and 600 A in both ac and dc modes. Additionally, both are compatible with the new iFlex™ flexible current probe (sold separately) which expands the measurement range to 2500 A ac and provides increased display flexibility, ability to measure around awkward sized conductors and improved wire access.

These clamps have proprietary inrush current measurement technology to capture motor starting current

- Measure current upto 600A AC/DC & voltage upto 600V AC/DC, CAT IV 600V, CAT III 1000V safety rating
- Proprietary inrush current measurement technology to capture motor starting current
- iFlex flexible current probe (sold separately) to expands measurement range upto 2500A AC



iFlex2500-18

Specifications	
Function	Parameter
Jaw Opening	1.33" (34mm)
Max Wire Size	750 MCM
Current Range AC (RMS)	0 - 600 A
Accuracy AC Current (50/60Hz)	2% +/- 5 counts
AC Response	True-rms
Current Range DC	0 - 600 A
Accuracy DC Current	2% +/- 5 counts
Voltage Range AC	0 - 600 V
Accuracy AC Voltage	1.5% +/- 5 counts
Voltage Range DC	0 - 600 V
Accuracy DC Voltage	1% +/- 5 counts
Resistance Range	0 - 6000Ω
Mechanical, Environmental and Safety Ratings (Category Ratings)	600 V CAT IV 1000 V CAT III